

# Diversified Silicone Products, Inc.

13937 Rosecrans Ave.

Santa Fe Springs, CA 90670

Tel: (562) 404-8942 Fax: (562) 404-1323

**Other Data Sheets Are Available On Our Website**

**www.diversifiedsilicone.com**



## SILICONE SHEETING

“DSP40MS”

MEDIUM STRENGTH GRADE

40 Shore “A”

### DESCRIPTION:

Medium Strength Grade silicone sheeting is designed to be used in applications where high physical properties are required without going to our high strength grade. The material is available in continuous rolls or sheets. It is resistant to extreme high and low temperatures, and is proven to be an excellent gasketing material. Available in many colors. Red and grey are standard. Sheet thickness ranges from 1/64” up to 1” thick. Available width is up to 60” wide. Call customer service for many other variations of this material.

### FEATURES:

- Excellent Gasketing Material
- Peroxide Free / Platinum Cured
- Non Blooming because it is peroxide free
- Extreme High & Low Temperature Resistant
- UV / Ozone Resistant
- Non- Toxic, Chemically Inert
- All FDA approved Ingredients
- Low Compression Set
- Fungus Resistant

### PHYSICAL PROPERTIES

PROPERTIES	Test Method	Typical Properties
Specific Gravity, G/CC	ASTM D297	1.14
Durometer, Shore “A”	ASTM D2240	40 +/-5
Tensile Strength, psi	ASTM D412	1000
Elongation, %	ASTM D412	850
Tear, ppi Die “B”	ASTM D624	100
Temperature Range	(°F)	-103 to +450

The above values are typical properties and are provided for information only. They should not be used to set specification requirements. It is up to the end user to determine whether the material is suitable for the intended application.