

Diversified Silicone Products, Inc.

13937 Rosecrans Ave.

Santa Fe Springs, CA 90670

Tel: (562) 404-8942 Fax: (562) 404-1323

Other Data Sheets Are Available On Our Website

www.diversifiedsilicone.com



SILICONE SHEETING

“DSP80CG” COMMERCIAL GRADE 80 Shore “A”

DESCRIPTION:

Commercial Grade silicone sheeting is designed to be used in applications where physical properties are not critical but extreme temperature resistance is still needed. Material is available in 25-80 durometer in many colors. Sheet thickness ranges from .010” to 1” thick. Available width is up to 75” wide. Call customer service for many other variations of this material.

FEATURES:

- Excellent Gasketing Material
- Extreme High & Low Temperature Resistant
- UV / Ozone Resistant
- Non- Toxic, Chemically Inert
- Fungus Resistant

PHYSICAL PROPERTIES

PROPERTIES	Test Method	Typical Properties
Specific Gravity, G/CC	ASTM D297	1.55
Durometer, Shore “A”	ASTM D2240	80 +/-5
Tensile Strength, psi	ASTM D412	650
Elongation, %	ASTM D412	275
Tear, ppi Die “B”	ASTM D624	80
Temperature Range	(°F)	-80 to +450 (+500 Intermittent)

The above values are typical properties and are provided for information only. They should not be used to set specification requirements. It is up to the end user to determine whether the material is suitable for the intended application.